

Wire vises

Part no.	A	B	C	Wire dia.	Weight	Description
	mm	mm	mm	mm	kg	
E128	510	520	160	20-28	29.8	With swing
E134-B	510	600	160	20-34	35.5	With swing and brake

E128 and E134 are delivered with extra jaws for wire dia. 12-22 mm.

Wire vise

With motor

Part no.	A	B	C	Wire dia.	Weight	Description
	mm	mm	mm	mm	kg	
E134-M	510	600	160	20-34	67.0	With motor for 380/220/110V (Standard 380V)

Wire vise

Part no.	A	B	C	Wire dia.	Weight	Description
	mm	mm	mm	mm	kg	
E250	700	700	250	20-50	116.0	With swing and brake

Are delivered with 3 set changeable dies for wirerope dia. 20-50 mm.

Wire vise

With motor

Part no.	A	B	C	Wire dia.	Weight	Description
	mm	mm	mm	mm	kg	
E250-M	980	700	250	20-50	156.0	With motor for 380/220/110V (Standard 380V)
E250H-M	980	700	250	20-50	165.0	With motor for 380/220/110V (Standard 380V)

E250-M are delivered with 3 set changeable dies for wirerope dia. 20-50 mm.

E250-M maximum wire rope diameter 38 mm.

E250H-M maximum wire diameter 44 mm.

E250-M maximum combination rope diameter 50 mm.

