

BMM Trawl blocks

Roller bearing · Thrust bearing on top · Galvanized

| Part no. | WLL 5:1 ton | Max load on headfitting ton | Test load ton | A mm | B mm | B ₁ mm | D mm | E mm | F mm | F ₁ mm | G mm | J mm | Max wire mm | Weight kg |
|----------|-------------------|-----------------------------------|---------------------|---------|---------|----------------------|---------|---------|---------|----------------------|---------|---------|-------------------|--------------|
| *K370-2A | 13.0 | 26.0 | 52 | 580 | 140 | 140 | 370 | 260 | 120 | 245 | 285 | 12 | 28 | 115.0 |
| *K400-2A | 15.0 | 30.0 | 55 | 670 | 180 | 180 | 400 | 245 | 180 | 305 | 300 | 15 | 28 | 185.0 |
| KH400-2A | 20.0 | 40.0 | 70 | 685 | 180 | 180 | 400 | 285 | 180 | 334 | 300 | 20 | 28 | 225.0 |
| K500-2A | 20.0 | 40.0 | 70 | 785 | 180 | 180 | 500 | 285 | 185 | 345 | 380 | 20 | 30 | 275.0 |
| K600-2A | 30.0 | 60.0 | 95 | 910 | 180 | 180 | 600 | 310 | 190 | 380 | 480 | 20 | 34 | 360.0 |
| K650-2A | 30.0 | 60.0 | 95 | 985 | 240 | 220 | 650 | 335 | 225 | 415 | 500 | 20 | 34 | 500.0 |
| KH650-2A | 40.0 | 80.0 | 120 | 975 | 240 | 220 | 650 | 337 | 225 | 415 | 500 | 20 | 38 | 530.0 |
| K800-2A | 40.0 | 80.0 | 120 | 1125 | 240 | 220 | 800 | 325 | 240 | 440 | 600 | 20 | 38 | 750.0 |
| KH800-2A | 60.0 | 120.0 | 165 | 1200 | 240 | 230 | 800 | 400 | 242 | 500 | 600 | 25 | 40 | 895 |
| K1000-2A | 60.0 | 120.0 | 165 | 1485 | 260 | 240 | 1000 | 485 | 270 | 570 | 825 | 25 | 44 | 1320.0 |
| K1200-2A | 70.0 | 140.0 | 195 | 1640 | 260 | 240 | 1200 | 440 | 264 | 530 | 1020 | 30 | 44 | 1750.0 |

* Are only supplied with full sideplates.

BMM-Blocks must be ordered with one of the following:

- E Swivel eye.
- F Swivel fork.
- S Swivel shackle eye.
- I Icedavit eye.

On order add letter, e.g. K500-2AE

Against extra charge all blocks are available with:

- C Tested with certificate.
- H Flame hardened sheave.

On order add letter, e.g. K500-2AEG

