

Shackles

Stainless steel · Bow type

| Part no. | WLL 5:1 ton | A mm | B mm | C mm | D mm | E mm | Weight kg/100 |
|----------|-------------------|---------|---------|---------|---------|---------|------------------|
| F04HSS | 0.06 | 4.0 | 4 | 8 | 16 | 14 | 1.0 |
| F05HSS | 0.12 | 5.0 | 5 | 10 | 20 | 17 | 2.0 |
| F06HSS | 0.15 | 6.0 | 6 | 12 | 24 | 21 | 4.0 |
| F08HSS | 0.3 | 8.0 | 8 | 16 | 32 | 28 | 7.0 |
| F10HSS | 0.4 | 9.5 | 10 | 20 | 40 | 34 | 7.0 |
| F12HSS | 0.6 | 12.0 | 12 | 24 | 48 | 42 | 25.0 |
| F16HSS | 1.0 | 16.0 | 16 | 32 | 58 | 56 | 40.0 |
| F19HSS | 1.5 | 20.0 | 20 | 38 | 66 | 65 | 60.0 |
| F22HSS | 2.0 | 22.0 | 22 | 44 | 77 | 77 | 90.0 |
| F25HSS | 3.0 | 25.0 | 25 | 50 | 88 | 87 | 110.0 |
| F32HSS | 3.5 | 32.0 | 32 | 64 | 112 | 112 | 240.0 |

Not for lifting applications.

