

Terminals for connectors

Part no.	A	A ₁	B	C	D	F	G	Dia.	For connector	Dia. after pressing	Weight	Swaging dies	Required pressure
	mm	mm	mm	mm	mm	mm	mm	mm	no	mm	kg		ton
NE14C	26.5	26.5	48	106	14.5	58	26	32	13	28	0.6	DIE-NE-28	250
NE16C	26.5	26.5	48	106	16.5	60	26	32	13	28	0.6	DIE-NE-28	250
NE18C	29.0	34.0	60	133	18.5	69	34	41	16/19	36	1.2	DIE-NE-36	300
NE20C	29.0	34.0	60	141	20.5	78	34	41	16/19	36	1.2	DIE-NE-36	300
NE22C	34.0	39.0	72	161	22.5	84	39	41	19	36	1.6	DIE-NE-36	300
NE24C	34.0	39.0	72	169	24.5	91	39	41	19	36	1.6	DIE-NE-36	300
NE26C	38.0	41.0	78	185	27.0	100	41	51	22	44	2.5	DIE-NE-44	600
NE28C	38.0	48.5	78	193	29.0	107	41	51	22/26	44	2.5	DIE-NE-44	600
NE30C	38.0	48.5	78	201	31.0	116	41	51	22/26	44	2.5	DIE-NE-44	600
NE32C	38.0	48.5	78	211	33.0	125	41	51	22/26	44	2.5	DIE-NE-44	600
NE34C	40.0	49.0	90	240	35.0	131	44	56	26	48	3.4	DIE-NE-48	600
NE36C	40.0	49.0	90	250	37.0	140	44	56	26	48	3.3	DIE-NE-48	600

